

**Legacy Lockers**  
**Locker Specifications**  
**Section 105100 - Wood Lockers**

**Part 1 - General**

**1.01 Section Includes**

Provide wooden lockers, end and filler panels and related items as specified.

**1.01 Submittals**

- A. Shop drawings showing individual locker construction, materials, dimensions, room layout, overall dimensions for installation and installation details including end and filler panels, crown molding, trim and accessories provided upon request.
- B. Stain and color chip samples for both wood and laminate doors are available upon request.

**1.02 Product Handling**

Store lockers and related products in a dry, climate controlled area in order to protect finished from damage during handling.

**Part 2 - Products**

**2.01 Materials**

- A. Furnish wooden lockers manufactured by:
  - Legacy Lockers
  - 4433 Bronze Way
  - Dallas, TX 75236
  - Phone (866) 937-1088
  - Fax (214) 466-1789
  - [www.LegacyLockers.com](http://www.LegacyLockers.com)
- B. Locker Box
  - a. Locker frame constructed of 5/8" stain resistant, high impact, high density thermally fused almond colored melamine with particleboard substrate. Leading edges of frame finished with a 2 mm PVC edge banding to closely match locker door. Additional frame materials available upon request.
  - b. Locking systems: **\*\*\*SELECT ONE\*\*\*** Heavy duty cam key locks furnished with two (2) keys per lock and two (2) master keys standard on all lockers. Padlock Hasp, High Security Hasp, Built-In MasterLock Combination Lock, Assa Abloy Card Lock, Coin Collect or Return Lock, Safe-O-Mat Coin Collect or Return, Digilock Temporary or Permanent Locks are also available. Additional locks available upon request.
  - c. Hinges: Two (2) heavy duty, steel European concealed hinges with up to 130 degrees of door opening on all doors 42" or less. Three (3) hinges on all doors over 42".
  - d. Hardware: One (1) coat rod and one (1) coat hook are standard on all full and half length lockers. Hardware available in brass, chrome and black finish. Additional hardware finishes available upon request. Note: Some lock finishes are limited.
  - e. Venting: 1/2" opening between door and frame on locker top and bottom provide unrestricted airflow.
  - f. Number Disk: 1-1/2" disc with black engraved number routed flush with locker door.
- C. Locker Doors **\*\*\*SELECT ONE\*\*\***
  - a. Laminate: 5/8" industrial grade core with .030" vertical grade plastic laminate. Door edge edge-banded with 2 mm PVC offered in a variety of colors to match or closely complement selected laminate.
  - b. Slab Veneer: 3/4" A-1 plain sliced veneer on industrial grade MDF core. Red Oak, Maple, Cherry, Mahogany or Walnut. Additional wood species and/or cuts are available upon request.

- c. Flat/Recessed Panel: 3/4" kiln dried solid wood stile and rail with flat/recessed center panel. All style and rail joints are glued together with moisture resistant glue for increased durability. Door edges are rounded. Red Oak, Maple, Cherry, Clear or Knotty Alder, Walnut or Mahogany. Additional wood species are available upon request.
  - d. Raised Panel: 3/4" kiln dried solid wood stile and rail with raised center panel. All style and rail joints are glued together with moisture resistant glue for increased durability. Door edges are rounded. Red Oak, Maple, Cherry, Clear or Knotty Alder, Walnut or Mahogany. Additional wood species are available upon request.
  - e. Raised Panel Louver: 3/4" kiln dried solid wood stile and rail with raised panel and louvers. All style and rail joints are glued together with moisture resistant glue for increased durability. Door edges are rounded. Louvers are in fixed position. Red Oak, Maple, Cherry, Clear or Knotty Alder, Walnut or Mahogany. Additional species are available upon request.
  - f. Louver: 3/4" kiln dried solid wood stile and rail with louvers. All style and rail joints are glued together with moisture resistant glue for increased durability. Louvers are in fixed position. Red Oak, Maple, Cherry, Clear or Knotty Alder, Walnut or Mahogany.
  - g. Ends and Fillers: Locker end, filler and back panels matching locker door cover exposed sides, backs and intersections.
- D. Finish: Multiple finishes and stains available. All wood surfaces are finished using a catalyzed polymer lacquer applied in two coats with hand sanding in between coats and sealed with moisture resistant top coat.

## **2.02 Fabrication:**

Fabricate locker parts square and rigid without warp with the finished faces flat and free of scratches and chips.

## **Part 3 – Execution**

### **3.01 Installation**

- A. Install lockers and accessories per approved plans and manufacturer's instructions for a plumb, rigid and flush installation.
- B. If Legacy Lockers is NOT contracted for installation it is the responsibility of the customer to arrange the unloading of the lockers and related items off the delivery truck.
- C. Lockers to be installed on a 2"x4" or 2"x6" base per design drawing, supplied either by manufacturer or by owner according to contract. Base extending from the wall 2" less than the locker depth. Locker connector hardware and installation instructions are provided by manufacturer.
- D. Anchor lockers to wall studs or furring strips attached to wall through locker back and to the base through the locker floor. Attach lockers together through predrilled holes with manufacturer supplied connectors.
- E. Adjust doors and hinges to accommodate uniform spacing after installation of lockers. Verify all working parts of locker including hinge and lock function. Attach number disks in specified sequence using adhesive. Clean lockers and deliver keys and pertinent information to appropriate individual.

## **Part 4 – Warranty**

### **4.01**

All wood parts and hardware shall be structurally sound and free from defects in material and workmanship under normal use and service for a period of three (3) years from date of delivery. All locking mechanisms are warranted for one (1) year.

Manufacturer reserves the right to modify, change or alter the design and/or specifications without prior notice.